



**acniti LLC**  
1-2-9 Nyoidani  
Minoh Osaka  
562-0011  
Japan

**acniti**

## ozone leak detector phnx-100

Reliable ozone measurement, easy to use! The Ozone Leak Detector PHNX-100 is a high-quality ozone gas detector that is specially designed for real-time measurement of ozone concentrations in the air. Whether you work with ozone generators for disinfection, in a laboratory environment, or are responsible for air quality in technical installations, this detector offers the certainty you need. Ozone is powerful, but potentially harmful if exposed to too much. The PHNX-100 ensures that you always have insight into the current situation. The detector is equipped with an accurate electrochemical sensor. If set values are exceeded, an alarm is automatically activated, possibly linked to external systems via a relay output. Installation is simple and operation is intuitive. The sensor is replaceable without recalibration, which saves time and costs in maintenance. The compact housing makes the detector suitable for a wide range of spaces, from technical installations to industrial workplaces. In short: the Ozone Leakage Detector PHNX-100 combines reliability, safety and ease of use and safety in one smart solution. Ideal for those who work with ozone and want to leave nothing to chance.



# ozone leak detector phnx-100

## ozone leak detector phnx-100

- ✓ Reliable real-time ozone concentration measurement
- ✓ Alarm function when threshold values are exceeded
- ✓ Easy installation and operation
- ✓ Sensor replaceable without recalibration
- ✓ Optional CT-value monitoring

## safety at a glance. measure ozone with precision.

Working with ozone offers great benefits — but also comes with risks. Ozone is a powerful oxidizer that, in high concentrations, can be harmful to human health and sensitive equipment. The PHNX-100 Ozone Leak Detector is specifically designed for reliable and continuous monitoring of ozone concentrations across a wide range of applications. This ensures your processes remain safe and your people stay protected.

## what does the ozone leak detector deliver?

The key benefit is safety. This detector provides real-time insight into the presence of ozone in the air and immediately triggers an alarm when threshold values are exceeded. As a result, you avoid not only health hazards, but also unnecessary process interruptions or liability in case of an incident.

In addition, the device is built for ease of use. It's quick to install, requires minimal maintenance, and the sensor can be replaced without the need for recalibration. This gives you maximum control with minimal effort.

## who is this detector essential for?

The PHNX-100 is ideal for any environment where ozone is generated or used. This includes companies using ozone for air or water purification, installers of HVAC or disinfection systems, laboratories, or industrial facilities with strict air quality requirements. It's also increasingly used in utility buildings and facility management as an extra layer of protection.

## optional feature: ct-value monitoring

For users who need deeper insight into total ozone exposure, an optional module is available to track the CT value (concentration × time). This provides added assurance, especially for validating disinfection processes or ensuring compliance in sensitive environments.

## The PHNX-100 Ozone Leak Detector for dependable ozone monitoring

| Specification          | Details                                                        |
|------------------------|----------------------------------------------------------------|
| Measuring Range        | 0–1 ppm or 0–10 ppm (depending on model)                       |
| Sensor Type            | Electrochemical                                                |
| Detection Type         | Diffusion                                                      |
| Display                | LCD screen                                                     |
| Alarm Function         | Visual and acoustic alarm; relay output                        |
| Relay Output           | 1× relay (NO/NC), max 3A @ 250V AC                             |
| Output Signal          | DC 4–20 mA or DC 0–10V                                         |
| Power Supply           | AC100V±10% 50/60Hz or DC24V±4V<br>Please specify when ordering |
| Power Consumption      | 10W                                                            |
| Operating Temperature  | 0°C to 40°C (32°F to 104°F)                                    |
| Operating Humidity     | 15%–95% RH (non-condensing)                                    |
| Dimensions (L × W × H) | 154 × 113 × 76 mm                                              |
| Weight                 | Approx. 1 kg                                                   |
| Mounting Method        | Wall-mounted                                                   |
| Sensor Replacement     | Replaceable without recalibration                              |
| Optional Feature       | CT-value (Concentration × Time) monitoring                     |